

# LTF09 "ACTIVE" SERIES WEIGHING KIT FOR LIFT TRUCK FORKS



LTF09 with optional remote control

Pair of forks with an integrated weighing system, for lift trucks; easy to use, sturdy, and reliable. Simple and easy to install, these replace the original forks and allow a clear visualisation of the loaded weight. Functions with 4 AA batteries, also rechargeable, with an approximate 40-hour battery life. Compatible with any lift truck having a DIN 15173 - FEM fork holder plate, of the IIA, IIB, or IIIA class. Available CE-M approved.

## MAIN FEATURES

- Weight indicator with membrane keyboard, 5 keys, IP68 stainless steel case, installed directly on a fork and connected to the other fork by means of a cable.
- LCD Display with 6 digits 25mm high, easily visible in any lighting condition
- Steel bearing structure
- Each fork weighs 75 kg (LTF25) and 90 kg (LTF50).
- Functions with 4 shear-beam IP68 load cells
- Accuracy: +/- 0.1% of the capacity
- Max. allowable overload: 300% of the nominal capacity.
- Max. horizontal inclination (flexibility): +/- 2° with the same accuracy characteristics.
- Power supply through rechargeable battery
- 4 AA batteries with extractable fitted drawer, attached to the forks.
- The operating time is of about 40 hours of continuous use or three months with the typical non continuous use, thanks to its auto switch-off function

## DIMENSIONS



	A	B	C	D	E	F	G	H	I
LTF0925A	1160	146	1300	317	720	110	382	76	65
LTF0925B	1160	146	1300	317	800	110	382	152	65
LTF0950A	1160	190	1300	367	932	110	477	76	80

## SELECTABLE FUNCTIONS

- High Resolution Weighing x 10
- Net/Gross or lb/kg conversion
- Weighs totalisation
- Formulation
- +/- Check
- Percentage weighing
- Alibi memory, for weight approved transmission (optional)
- Counting
- Input/Output
- Hold and Peak

## KEYBOARD FUNCTIONS

- Zeroing, semi automatic tare, presettable tare, function mode, stand-by
- NOTES:** functions available also with optional infrared remote control.

## Available versions

Code	Plate	Max Capacity kg	Division kg
LTF0925A	FEM2A	500 / 1000 / 2500	0,5 / 1 / 2
LTF0925AM	FEM2A	2500	2
LTF0925B	FEM2B	500 / 1000 / 2500	0,5 / 1 / 2
LTF0925BM	FEM2B	2500	2
LTF0950A	FEM3A	5000	5
LTF0950AM	FEM3A	5000	5

## Options only available at time of order

Code	Description
DFTL	Remote control for use up to 8m, configurable as a single tare key or four keys

## Accessories

Code	Description
TECMAN	Printed technical manual (free, if downloaded from the web) NET PRICE
UMAN	Printed user manual (free, if downloaded from the web) NET PRICE

---

Dini Argeo S.r.l.

Copyright - All Rights Reserved -  
[Privacy Policy](#)

[www.diniargeo.com](http://www.diniargeo.com)